

**HTL 4010, HTL 3510 and HTL 3210
New 10 m Haulotte telescopic handlers**

Placing the needs of our customers as the principle focus for our company, has enabled Haulotte, the world's 3rd largest manufacturer of Aerial Work Platforms to develop a full line of products which are of the highest safety standard and amongst the most innovative in the world.

Designed to place loads at heights up to 10 m, the new range of Telehandlers Models HTL 4010, 3510 and 3210 are targeted to the construction market and industry in general. The 3 new machines, add to Haulotte's existing popular 14 and 17 metre product range.

The three new HTL's set a new standard in Telehandler lifting performance by providing improved maximum lifting capacity and reach whilst keeping the overall length under a compact 5 m.

With the new Haulotte HTL 10 m Telehandler range, the professionals of the construction and general industry will not have to choose between compactness and performance. They will get the best of both worlds in one product.

The Haulotte HTL 4010, 3510 and 3210 retain the operational precision and user comfort found in the bigger Haulotte Telehandler series by incorporating Hydrostatic transmission and full proportional joystick control as standard features.

Each of the 3 new HTL Telehandlers enables Haulotte to offer optimised solutions in the 10 metre lift height range, providing leading job site performance and return on investment.

Compact and strong

The 3 new HTL 10 m share a common compact design:

- True 10 m with over 10 m maximum fork height (fork reach 10m)
- Industry leading 7.2 m maximum forward reach.
- Compact 5 m overall length, which translates into superior manoeuvrability.
- Low profile boom design provides maximum visibility on the right hand side of the Telehandler.

Both the HTL 4010 and 3210 are fitted with compact stabilizers that when deployed, form an 2.26 m overall width footprint to permit load lifting in confined working spaces.

The HTL 3510 is also equipped with frame levelling for optimised mobility and accelerated load positioning.





Leading lifting performance

HTL 4010 with Stabilizers

4000 kg maximum lifting capacity

1200 kg at maximum reach

HTL 3210 with Stabilizers

3200 kg maximum lifting capacity

850 kg at maximum reach

HTL 3510 with frame leveling

3500 kg maximum lifting capacity

500 kg at maximum reach

Haulotte Group

Press Contact: Marjolaine Degrange

Tel : +33 4 77 29 21 58 – e-mail : mdegrange@haulotte.com

Internet Website: www.haulotte.com

